

Zener Diode Barrier

MTL7787+



Features

- ▶ Simple installation onto standard DIN railing
- ▶ Removable colour-coded terminals for easy connection
- ▶ Can accommodate conductors up to 2.5 mm²
- ▶ Supports up to two zones of I.S. products

Description

Model MTL7787+ is an intrinsically safe, zone-powered, Zener-diode barrier for use in conventional fire detection systems for protection within hazardous areas.

Each Zone contains two stages of pulse-tested Zener or forward- connected diodes and an 'infallible' terminating resistor. In the event of an electrical fault in the safe area, the diodes limit the voltage that can reach the hazardous area and the resistor limits the current. A fuse protects the diodes, and the two stages of voltage limitation ensure continued safety if either stage should fail. No active output-current limiting circuits are employed.

Model MTL7787+ is certified 'ia' for all zones and 'IIC' for all explosive atmospheres.

PLEASE NOTE: The Earth connections to the unit are made via connection to the DIN rail (this product MUST be earthed).

Specification

Ordering Code	MTL7787+
Maximum voltage of Zener diode when fuse blows	28 V
Minimum value of terminating resistor	300 Ω
Maximum short-circuit current	93 mA
Number of Channels	2
Maximum end-to-end resistance	333 Ω
Working Voltage	26.6 V
Maximum Voltage	27.2 V
Fuse Rating (continuous)	50 mA
Operating Temperature Range	-20 °C to + 60 °C (continuous working)
Storage Temperature Range	-40 °C to + 80 °C
Maximum Humidity	95%RH - Non Condensing (at 40 °C)
Weight (g) / Dimensions (mm)	140 / H90 x W105 x D12.6
Mounting Methods	DX070 Box, SMB-2 or SMB-3 Enclosures

FURTHER INFORMATION: www.mtl-inst.com

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.